

# HP ProLiant Essentials Rapid Deployment Pack—Linux Edition Installation Guide

Release 1.00



October 2003 (First Edition)  
Part Number 347244-001

© Copyright 2003 Hewlett-Packard Development Company, L.P.

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Pentium® are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a U.S. registered trademark of Linus Torvalds.

PostgreSQL Database Management System (formerly known as Postgres, then as Postgres95)  
Portions Copyright 1996–2002, The PostgreSQL Global Development Group  
Portions Copyright 1994, The Regents of the University of California

Printed in the U.S.A.

HP ProLiant Essentials Rapid Deployment Pack—Linux Edition Installation Guide

October 2003 (First Edition)  
Part Number 347244-001

---

# Contents

## About This Guide

Audience Assumptions .....	v
Related Documents .....	v
Where to Go for Additional Help .....	vi
Online Resources .....	vi
Telephone Numbers .....	vi

## Chapter 1

### Licensing

Overview .....	1-1
Licensing Options .....	1-1
Obtaining Licenses .....	1-2
Evaluation Licenses .....	1-2
Purchased Licenses .....	1-2
Applying a License File .....	1-3
Applying Licenses During a First-Time Installation .....	1-3
Adding Licenses to an Existing Installation .....	1-3
Replacing Licenses in an Existing Installation .....	1-4

## Chapter 2

### First-Time Installation

Overview .....	2-1
Deployment Infrastructure .....	2-2
Basic Deployment Infrastructure .....	2-2
Multi-Server Deployment Infrastructure .....	2-3
Installation Requirements .....	2-4
Network Infrastructure Requirements .....	2-4
System Requirements .....	2-4
Basic Installation .....	2-7
Altiris Deployment Server for Linux .....	2-9
ProLiant Integration Module for Linux Deployment Server .....	2-16
ProLiant Integration Module for NFS Server .....	2-21
Multi-Server Installation .....	2-25

## Chapter 3

### Upgrading

Overview .....	3-1
----------------	-----

## Chapter 4

### Pre-Deployment Configuration for the Deployment Server

Overview .....	4-1
Configuring the Access Settings for the Deployment Server for Linux Web Console.....	4-2
Synchronizing the Web Console Display Name with the Linux Name .....	4-4
Modifying the Primary Lookup Key.....	4-5
Configuring ProLiant BL Server Enclosures .....	4-8
ProLiant BL e-Class Servers .....	4-9
ProLiant BL p-Class Servers .....	4-10
Creating Physical Boot Diskettes for Server Deployment .....	4-12

## Chapter 5

### Pre-Deployment Configuration for Linux Scripted Installs

Overview .....	5-1
Preconfiguring the ProLiant Support Pack for Linux .....	5-2
Preconfiguring Deployment Settings for Red Hat Linux Scripted Install Jobs .....	5-3
Preconfiguring Deployment Settings for UnitedLinux Scripted Install Jobs.....	5-5

## Appendix A

### Manually Installing Red Hat Enterprise Linux Boot Files

## Appendix B

### Manually Installing Linux Distribution CDs

## Index

---

## About This Guide

This guide provides detailed information for installing the Rapid Deployment Pack—Linux Edition. It describes the process for pre-deployment configuration of the Altiris Deployment Server for Linux and the provided Linux scripted-install jobs and installation files. Instructions for upgrading the Deployment Server and NFS server with new versions of software are also provided.

## Audience Assumptions

To install and configure the Rapid Deployment Pack, it is assumed that you have knowledge of:

- Installing Linux either from CD or by means of a network
- Basic Linux command line interface operations (for example, mounting and unmounting floppy and CD-ROM drives, creating directories, and copying files)
- Network infrastructure

To perform tasks after the installation is complete, it is assumed that you have knowledge of editing files within Linux and running scripts under Linux.

## Related Documents

HP recommends reviewing the following documentation before reading this guide:

- The *HP ProLiant Essentials Rapid Deployment Pack Planning Guide* provides information about how to best use the Rapid Deployment Pack as a server deployment solution. Review this document before beginning the software installation.
- The *HP ProLiant Essentials Rapid Deployment Pack—Linux Edition Support Matrix* for your Rapid Deployment Pack version details which servers and operating systems are supported for deployment.

HP recommends reviewing the following documentation after reading this guide:

- The *HP ProLiant Essentials Rapid Deployment Pack—Linux Edition User Guide* provides information on using the Rapid Deployment Pack as a server deployment solution. It describes the directory structure and files provided with each Rapid Deployment Pack component along with their respective uses and provides example deployments.

All of the documents can be found at <http://www.hp.com/servers/rdp>, on the product CD in .pdf format under /pim-lds/docs, and on the Deployment Server after the Rapid Deployment Pack installation under /opt/altiris/deployment/adlserver/docs.

## Where to Go for Additional Help

### Online Resources

- HP ProLiant Essentials Rapid Deployment Pack website at <http://www.hp.com/servers/rdp>
- HP ProLiant Essentials Rapid Deployment Pack Knowledge Base at <http://www.hp.com/servers/rdp>
- ITRC User Forum “ProLiant Deployment, Provisioning (RDP, SmartStart)” at <http://forums.itrc.hp.com>
- Altiris website at <http://www.altiris.com>

### Telephone Numbers

For the name of your nearest HP authorized reseller:

- In the United States, call 1-800-345-1518.
- In Canada, call 1-800-263-5868.

For HP technical support:

- In the United States and Canada, call 1-800-652-6672.
- Outside the United States and Canada, refer to <http://www.hp.com>.

## Overview

This chapter describes the licensing options available for use with the Rapid Deployment Pack as a server deployment solution and how to purchase, install, and add licenses.

A license allows a server to be deployed and managed by the Altiris Deployment Server for Linux. One license is required for each server being managed. After a license is applied to a specific server, the license cannot be removed or transferred to another server.

A license file contains licenses for a predetermined number of servers. License files are applied without reference to the Rapid Deployment Pack version and are not specific to Rapid Deployment Pack—Windows Edition or Rapid Deployment Pack—Linux Edition, as long as the one license per server requirement is met.

## Licensing Options

The Rapid Deployment Pack offers five licensing options:

- **One-node license**—Use this license to deploy and manage deployment of one server through the Deployment Server.
- **10-node license**—Use this license to enable and manage deployment of 10 servers through the Deployment Server.
- **Flexible Quantity license**—Flexible Quantity license kits are available to obtain an exact quantity of licenses in the purchase of a single software option kit.
- **Activation Key Agreement**—This option provides the ability to order a key in the quantity desired and for a specific time and purchase a license for each server deployed over time.
- Licenses are also bundled with blade enclosures.

For more information about Flexible Quantity and Master licensing options, refer to the ProLiant Essentials Licensing Options at <http://www.hp.com/servers/rdp>.

## Obtaining Licenses

### Evaluation Licenses

Two types of evaluation licenses are available for use:

- A 10-node, seven-day evaluation license is built into the Deployment Server. No license file is required. The evaluation license is set up during the Deployment Server installation.
- To obtain and use a 10-node, 30-day evaluation license:
  1. Access <http://www.hp.com/servers/rdp/eval>.
  2. Follow the online instructions. An evaluation license file will be e-mailed to you.

### Purchased Licenses

To register your product and obtain your license file:

1. Locate the unique 20-character product registration number on the label **on the back** of the software-packaging box. The registration number is in the form:

xxxxxx-xxxxxx-xxxxxx-xxxxxx

**IMPORTANT:** Keep your product registration number for future reference.

2. Access <http://www.hp.com/servers/rdp/register>.
3. Follow the online instructions to complete the registration process. A license file will be e-mailed to you.

Additional purchased licenses can be transferred or combined with already registered licenses. Refer to the instructions at <http://www.hp.com/servers/rdp/register>.



## Applying a License File

### Applying Licenses During a First-Time Installation

To use the 10-node, seven-day evaluation license that is built into the Deployment Server, during the installation at the Altiris Deployment Server for Linux Configuration screen, press the **Enter** key when prompted to enter the License file path and name.

To use a purchased or evaluation license file, during the installation at the Altiris Deployment Server for Linux Configuration screen, enter the license file path and name in the **License file** field.

You can view the number of licensed nodes from the Web console using the **About** icon within the Web console toolbar.

### Adding Licenses to an Existing Installation

If you have purchased additional licenses for an existing installation, to add the new license file to your Deployment Server:

1. Copy the license file into the /opt/altiris/deployment/adlserver directory.
2. Change directory to /opt/altiris/deployment/adlserver.
3. Use the Altiris license script to input the new file by the following command:

```
./license filename.lic --restart
```

where filename is the name of the license file.

You can view the additional number of licensed nodes from the Web console using the **About** icon within the Web console toolbar.

## Replacing Licenses in an Existing Installation

If you have previously purchased licenses, have returned or transferred the licenses, and have obtained a new license file that is to replace your existing license file:

1. At the Deployment Server, copy the license file into the `/opt/altiris/deployment/adlserver` directory.
2. Change directory to `/opt/altiris/deployment/adlserver`.
3. Use the Altiris license script to input the new file by the following command:  

```
./license filename.lic --replace --restart
```

where `filename` is the name of the license file.
4. When prompted, answer **Y** to replace all license Activation Keys.

You can view the number of licensed nodes from the Web console using the **About** icon within the Web console toolbar.

---

## First-Time Installation

### Overview

This chapter describes requirements and procedures for installing the Rapid Deployment Pack for the first time. The following installation infrastructures are discussed:

- A basic deployment infrastructure consisting of all components on a single server.
- A multi-server deployment infrastructure in which the DHCP server and the NFS server can be separate from the Deployment Server.

## Deployment Infrastructure

### Basic Deployment Infrastructure

In a basic deployment infrastructure, all Deployment Server components are installed on one server. The following graphic illustrates this setup.

The Rapid Deployment Pack installation provides means for installing the following components on the Deployment Server:

- Alitiris Deployment Server for Linux
  - Deployment Server for Linux
  - DHCP Server (ISC)
  - Deployment Server Database (PostgreSQL)
  - Deployment Server for Linux Web Console
  - Deployment Server Client Access Point
  - Altiris PXE Server
- ProLiant Integration Module for Linux Deployment Server
- ProLiant Integration Module for NFS



## Multi-Server Deployment Infrastructure


In a multi-server deployment infrastructure, the DHCP server or the NFS server can be separate from the Deployment Server. The following graphic depicts the multi-server deployment infrastructure.

The Rapid Deployment Pack installation provides means for installing the following components on the Deployment Server:

- Altiris Deployment Server for Linux
  - Deployment Server for Linux
  - Deployment Server Database (PostgreSQL)
  - Deployment Server for Linux Web Console
  - Deployment Server Client Access Point
  - Altiris PXE Server
- ProLiant Integration Module for Linux Deployment Server

The Rapid Deployment Pack installation provides means for installing the following components on the NFS Server:

- ProLiant Integration Module for NFS



## Installation Requirements

This section describes the requirements to successfully install each component of the Rapid Deployment Pack.

### Network Infrastructure Requirements

The Rapid Deployment Pack is designed to perform optimally with DHCP and PXE in the network environment. DHCP and PXE are not required to use the Rapid Deployment Pack; however, if PXE is used to perform remote deployment of servers, DHCP must be installed and accessible on the network. Other alternatives, such as boot diskettes, are available. Two DHCP server setup options available with Rapid Deployment Pack include either DHCP running on the Deployment Server or running DHCP on a separate server in the network.

If you choose to install DHCP on the Deployment server, you must use the DHCP server included with the Rapid Deployment Pack. DHCP is provided as part of the Rapid Deployment Pack installation.

If you have an existing DHCP server that supports PXE, no additional installation steps are needed for PXE to function. Do not use the Rapid Deployment Pack installation to install DHCP on the separate server.

### System Requirements

The following system requirements for the deployment server, NFS server, and target servers must be met before installing the Rapid Deployment Pack. A separate NFS server is not required but is supported.

#### Linux Deployment Server

The deployment server hardware and network configuration must be:

- An Intel® Pentium® III or higher processor
- At least 256 MB RAM
- A CD-ROM drive
- A network connection, configured with a static IP address and hostname
- Set with the current date and time for the Deployment Server using ROM-Based Setup Utility (RBSU).

The deployment server software and configuration must be:

- Red Hat Enterprise Linux AS 2.1 Update 2, Red Hat Enterprise Linux ES 2.1 Update 2, or UnitedLinux 1.0 installed

**NOTE:** UnitedLinux 1.0 refers to Conectiva Enterprise Linux, SCO Linux Server 4.0, SuSE Linux Enterprise Server 8, and TurboLinux Enterprise Server 8 powered by UnitedLinux 1.0.

- ProLiant Support Pack for Linux to provide the latest supported network drivers for the deployment server
- A minimum of 4 GB of available disk space on /opt, plus additional space to store any captured disk images or application installation files

**NOTE:** The default Red Hat Enterprise Linux 2.1 install places /opt in /, which is only 384 MB.

- The SAMBA SMB server package with minimum version 2.2.1 must be installed before running the Rapid Deployment Pack installation. An adequate version of SAMBA is included with the Red Hat Enterprise Linux 2.1 and UnitedLinux 1.0 distributions.
- PostgreSQL client package will be installed during the Rapid Deployment Pack installation; however, if it is installed before Rapid Deployment Pack installation, version 7.2.2 or later is required. Red Hat Enterprise Linux 2.1 distribution contains postgresSQL with an earlier version than 7.2.2.
- To access the Web console, the minimum browser versions required for Linux are Mozilla 1.0.1 and Netscape 6.1. (A client running Windows will be able to access the Web console using either Netscape 6.1 or Internet Explorer 5.5 or later.)
- (Optional) The X Window System package (xpdf) for viewing .pdfs to view the Rapid Deployment Pack—Linux Edition documents on the source CD or on the Deployment Server under the ./docs directory after the Deployment Server installation is complete.
- If a firewall is installed on the server, the configuration must allow communication through the ports listed in Table 2-1:

**Table 2-1: Open Ports for Deployment Server Firewall Configuration**

Port	Function
TCP/402	Listens for client connections
UDP/402	Listens for server discovery packets
TCP/405	Listens for file transfer requests
TCP/5432	postgres server listens on this port
UDP/67	PXEServer when use DHCP option is set to true
UDP/4011	PXEServer
UDP/1759	PXEmtftp when Multicasting is enabled
UDP/69	tftp
TCP/1010	PXECfgServer
TCP/8080	Used by Tomcat

For the Rapid Deployment Pack installation, HP recommends having:

- A license file (for information on licensing, refer to Chapter 1 in this guide) for purchased licenses or 30-day evaluation licenses
- Red Hat Enterprise Linux distribution CD #1 available (required for populating boot files if Red Hat Enterprise Linux AS 2.1 or Red Hat Enterprise Linux ES 2.1 jobs are selected)

For additional information about requirements for the deployment server, refer to the *Altiris Deployment Server 5.6 for Linux Product Guide*, which can be found at <http://www.hp.com/servers/rdp>.

## Linux NFS Server

The Deployment Server can also be used as the NFS server, or a separate NFS server can be configured. The NFS server hardware and network configuration must consist of:

- A CD-ROM drive
- A network connection, configured with a static IP address, with DNS available on the network if a hostname will be used in the provided jobs

The NFS server software and configuration must consist of:

- If separate from the Deployment Server, Red Hat Linux 7.2, Red Hat Linux 7.3, Red Hat Linux 8.0 Professional, Red Hat Enterprise Linux AS 2.1 Update 2 or earlier, Red Hat Enterprise Linux ES 2.1 Update 2, or UnitedLinux 1.0
- ProLiant Support Pack for Linux to provide the latest supported network drivers for the NFS server
- At least 1.9 GB of available disk space on the /usr directory for each distribution that is installed from the Linux NFS server
- NFS software installed and configured (If a firewall is installed on the server, the configuration must allow incoming NFS connections, for example, UDP port 2049 for a typical NFS port.)

For the Rapid Deployment Pack installation, HP recommends having Red Hat Linux or UnitedLinux Distribution CDs available.

## Target Servers

The Rapid Deployment Pack supports ProLiant BL servers and select ProLiant ML/DL servers. For details on target server requirements, refer to the *HP ProLiant Essentials Rapid Deployment Pack—Linux Edition Support Matrix* for your version of Rapid Deployment Pack.



## Basic Installation

This section provides directions for installing the Rapid Deployment Pack on your server. This basic installation includes the Altiris Deployment Server for Linux, ProLiant Integration Module for Linux Deployment Server, and ProLiant Integration Module for NFS installed on the same server. The Altiris Deployment Server for Linux includes installation for DHCP, PXE, database, Web console, and client access point components.

To install software from the Rapid Deployment Pack—Linux Edition CD on the deployment server:

1. Insert the Rapid Deployment Pack—Linux Edition CD into the intended deployment server.
2. Log in as `root` at the intended deployment server.
3. Mount the CD:

```
mount /mnt/cdrom (Red Hat)
```

or

```
mount /media/cdrom (UnitedLinux)
```



## 4. Run the setup script:

```
/mnt/cdrom/setup.sh (Red Hat)
```


or

```
/media/cdrom/setup.sh (UnitedLinux)
```

**NOTE:** Do not change directory to the CD-ROM directory to run the setup script.


5. Read the license agreement displayed. When finished reading the agreement, enter **q**.

6. If you agree to the terms of the license agreement, enter **1** to **ACCEPT License Agreement** and press the **Enter** key.




## Altiris Deployment Server for Linux

1. Enter **1** to choose **Altiris Deployment Server for Linux** from the main menu, and press the **Enter** key to begin the installation process.




2. Enter **1** to choose **Start Installation**, and press the **Enter** key. This process will extract the files and install the Altiris Deployment Server for Linux components after the license agreement is accepted.




```
root@rdple:~  
File Edit Settings Help  
HP Rapid Deployment Pack - Linux Edition Installation  
Altiris Deployment Server for Linux  
  
Verify all system requirements are met regarding partitions and system  
services prior to installation. For detailed information refer to  
the installation guide found on the Rapid Deployment Pack cd.  
  
(1) Start Installation  
(2) Cancel Installation  
  
Selection ?
```

3. Read the license agreement displayed. When finished reading the agreement, enter **q**.




```
root@rdple:~  
File Edit Settings Help  
Altiris Deployment Server for Linux  
  
PLEASE READ THE FOLLOWING LICENSE AGREEMENT  
-----  
  
Please read the following License Agreement . Press thePAGE DOWN key to see the  
rest of the agreement.  
  
Software License Agreement  
IMPORTANT - READ CAREFULLY: This Altiris Software  
License Agreement ("License") is a legal agreement between you (either an  
individual or a single entity) and Altiris, Inc. ("Altiris") for the licensing  
of software products from Altiris. DO NOT DOWNLOAD, INSTALL, COPY OR USE THIS  
SOFTWARE UNTIL YOU HAVE READ AND ACCEPTED THIS LICENSE. BY DOWNLOADING,  
INSTALLING, COPYING, OR USING THIS SOFTWARE, YOU AGREE TO BE BOUND BY THIS  
LICENSE. IF YOU DO NOT AGREE WITH ANY TERM OR CONDITION OF THIS LICENSE,  
ALTIRIS IS NOT WILLING TO LICENSE THE SOFTWARE TO YOU. IN SUCH EVENT, YOU MAY  
NOT DOWNLOAD, INSTALL OR USE THE SOFTWARE. YOU MAY, HOWEVER, RETURN THE  
SOFTWARE (INCLUDING ALL ACCOMPANYING MEDIA, DOCUMENTATION, PACKAGING AND  
MATERIALS) IN AN UNDAMAGED CONDITION TO THE VENDOR FROM WHOM YOU ACQUIRED IT  
WITHIN 30 DAYS FOR A REFUND OF THE FEE, IF ANY, YOU PAID FOR THE LICENSE.This  
License governs seven (7) day and 10 Node evaluation licenses as well  
as all other licenses applicable to Altiris products. There is no fee for an  
Viewing Altiris License Agreement - Press q when finished
```


4. If you agree to the terms of the license agreement, enter **1** to **ACCEPT License Agreement** and press the **Enter** key.



5. At the Altiris Deployment Server for Linux Configuration screen, you are asked several questions regarding the DHCP and PXE servers, SAMBA user name and password, Database Password, and License file information. Press the **Enter** key to accept the **yes** default to **Install DHCP Server**.



6. Press the **Enter** key to accept the **yes** default to **Install PXE Server**.
7. Enter a **SAMBA User Name** and press the **Enter** key, or press the **Enter** key to use the default name.
8. Enter a **SAMBA Password** and press the **Enter** key.
9. Enter a **Database Password** and press the **Enter** key.
10. For the **License File**, either press the **Enter** key to select a free seven-day evaluation license or enter the path and filename of the Altiris license file and press the **Enter** key. For more information on licensing, refer to Chapter 1.
11. Enter **1** to **ACCEPT selections** and press the **Enter** key.



```
root@rdple:~
File Edit Settings Help

HP Rapid Deployment Pack - Linux Edition Installation
Altiris Deployment Server for Linux

-----
Altiris Deployment Server for Linux Configuration

Install DHCP Server  yes
Install PXE Server   yes
SAMBA User Name      leuser
SAMBA Password       password
Database Password    password
License File         /opt/altiris/deployment/adlserver/default.lic


-----

(1) ACCEPT selections
(2) CHANGE selections
(3) CANCEL Installation

Selection ? █
```


**NOTE:** The passwords used here are for illustrative purposes only. You will need to modify these passwords to reflect your particular environment.

12. After the Altiris Deployment Server for Linux installation, the **DHCP Server Basic Configuration** screen appears. Enter a **Network Subnet Address** and press the **Enter** key.



13. Enter the **Network Mask Address** and press the **Enter** key.
14. Enter the **Network Broadcast Address** and press the **Enter** key.
15. Enter the **Network Router Address** and press the **Enter** key. An IP address for a valid server must be entered.
16. Enter the **Start of Address Pool** IP address and press the **Enter** key.
17. Enter the **End of Address Pool** IP address and press the **Enter** key.


18. Enter **1** to **ACCEPT selections** and press the **Enter** key.



```
root@rdple:~  
File Edit Settings Help  
HP Rapid Deployment Pack - Linux Edition Installation  
Altiris Deployment Server for Linux  
-----  
DHCP Server Basic Configuration  
  
Network Subnet Address      10.10.10.0  
Network Mask Address       255.255.255.0  
Network Broadcast Address  10.10.10.255  
Network Router Address     10.10.10.1  
Start of Address Pool      10.10.10.100  
End of Address Pool        10.10.10.200  
-----  
  
(1) ACCEPT selections  
(2) CHANGE selections  
(3) CANCEL DHCP Server configuration and continue  
  
Selection ? █
```

**NOTE:** The addresses used here are for illustrative purposes only. You must modify these addresses to reflect your particular environment.


19. After the DHCP settings have been applied and verified, enter **1** to choose **Start Services** and press the **Enter** key.



```
root@rdple:~  
File Edit Settings Help  
HP Rapid Deployment Pack - Linux Edition Installation  
Altiris Deployment Server for Linux  
-----  
Deployment Server services must be started to continue the installation.  
  
(1) Start Services  
(2) Do not Start Services  
  
Selection ? █
```



20. The following screen confirms that the services have started and provides information for accessing the Web console. Enter **1** to choose **Finish Installation** and press the **Enter** key.



```
root@rdple:~
File Edit Settings Help

HP Rapid Deployment Pack - Linux Edition Installation
Altiris Deployment Server for Linux


Altiris Deployment Server for Linux is now running.
The Altiris Deployment Server for Linux web console can be reached at:
http://<ip_address_or_host_name_of_this_server>:8080/webconsole.

Refer to Chapter 4 for pre-deployment configuration modifications required
prior to using the Deployment Server.


(1) Finish Installation
Selection ? █
```

## ProLiant Integration Module for Linux Deployment Server

1. The Rapid Deployment Pack main menu appears. Enter **2** to choose **ProLiant Integration Module for Linux Deployment Server** and press the **Enter** key.



2. Enter **1** to choose **Start Installation** and press the **Enter** key.




- After the ProLiant Integration Module for Linux Deployment Server files are copied, a list of available deployment jobs displays.

For each set of jobs you want installed, enter the selection number for the jobs and press the **Enter** key. To select all jobs, enter the selection number for **SELECT all** and press the **Enter** key.

The provided deployment jobs consist of:

- **Red Hat and UnitedLinux Scripted Install Jobs** enable a scripted hardware configuration and operating system installation of Red Hat Linux or UnitedLinux to be performed on a ProLiant server.
- **Smart Start Toolkit and OS Imaging Jobs** enable capture of a server hardware configuration and an image of a server hard drive, including the operating system and software applications, and deploys this hardware configuration and image to unconfigured ProLiant servers.
- **SmartStart Toolkit Hardware Configuration Jobs** enable capture of an existing server's hardware configuration and deploys that configuration to other servers.




- When finished making your job selections, enter the selection number for **ACCEPT selections** and press the **Enter** key. This process will start the import of the jobs selected, which might take several minutes depending on number of jobs chosen.

5. If you select Red Hat Enterprise Linux AS 2.1, you are prompted to copy the Red Hat Enterprise Linux boot files required for scripted install jobs to the Deployment Server directory. Insert your Red Hat Enterprise Linux AS 2.1 Update 2 CD #1 when prompted. If the installation times out after one minute of looking for the CD, you will be prompted to either retry or to skip this step.

**IMPORTANT:** If you skip the Red Hat Enterprise Linux boot files copying steps at this time by choosing to **Skip this step** after the time-out, you can manually install these files at a later time. For instructions, refer to Appendix A in this guide.


**NOTE:** You are prompted for the Red Hat Enterprise Linux 2.1 CD #1 to copy the Linux boot files to the Deployment Server. The Red Hat Enterprise Linux distributions CDs are installed on the NFS server. Use the same CD distribution during the installations of the Deployment Server and NFS server.




6. If you select Red Hat Enterprise Linux ES 2.1, you are prompted to copy the Red Hat Enterprise Linux boot files required for scripted install jobs to the Deployment Server directory. Insert your Red Hat Enterprise Linux ES 2.1 Update 2 CD #1 when prompted. If the installation times out after one minute of looking for the CD, you will be prompted to either retry or to skip this step.

**IMPORTANT:** If you skip the Red Hat Enterprise Linux boot files copying steps at this time by choosing to **Skip this step** after the time-out, you can manually install these files at a later time. For instructions, refer to Appendix A in this guide.


**NOTE:** You are prompted for the Red Hat Enterprise Linux 2.1 CD #1 to copy the Linux boot files to the Deployment Server. The Red Hat Enterprise Linux distributions CDs are installed on the NFS server. Use the same CD distribution during the installations of the Deployment Server and NFS server.



- When prompted, place the Rapid Deployment Pack—Linux Edition CD in the CD-ROM drive.




- The following screen confirms the ProLiant Integration Module for Linux Deployment Server installation is complete. Enter **1** to choose **Finish Installation** and press the **Enter** key.




## ProLiant Integration Module for NFS Server

1. The Rapid Deployment Pack main menu appears. Enter **3** to choose **ProLiant Integration Module for NFS Server** and press the **Enter** key.




2. Enter **1** to choose **Start Installation** and press the **Enter** key.



3. A list of the supported Linux distributions that can be deployed with Rapid Deployment Pack is displayed. Selecting a Linux Distribution will copy the ProLiant Support Pack files for that distribution and begin the Linux distribution CD query process to copy the Linux files onto the NFS server.


For each distribution you want installed, enter the selection number for the specific distribution and press the **Enter** key. To select all distributions, enter the selection number for **SELECT all** and press the **Enter** key.

A screenshot of a terminal window titled 'root@rdple:~'. The window has a menu bar with 'File', 'Edit', 'Settings', and 'Help'. The main content area has a blue header with the text 'HP Rapid Deployment Pack Installation' and 'ProLiant Integration Module for NFS Server'. Below this, it says 'Select the distribution(s) that you wish to install on this NFS server.' followed by a green 'Install' prompt. A list of options is shown, each preceded by a green '[' and followed by a green ']'. The options are: (1) Red Hat Linux 7.2, (2) Red Hat Linux 7.3, (3) Red Hat Linux 8.0, (4) Red Hat Enterprise Linux AS 2.1, (5) Red Hat Enterprise Linux ES 2.1, (6) UnitedLinux 1.0, (7) SELECT all, (8) CLEAR all, (9) ACCEPT selections, and (10) CANCEL installation. A dashed line separates the first six options from the last four. At the bottom, it says 'Selection ?' followed by a cursor.

4. When you have finished making your Linux distribution selections, enter the selection number for **ACCEPT selections** and press the **Enter** key. This process will start the file copy and CD query process.
5. Once the ProLiant Support Pack files and distributions files are copied, you will be prompted for the Rapid Deployment Pack—Linux Edition CD. When prompted, place the CD in the CD-ROM drive.




6. The following screen confirms the ProLiant Integration Module for NFS Server installation is complete. Enter **1** to choose **Finish Installation** and press the **Enter** key.



## Installation Complete

The Rapid Deployment Pack main menu appears. Enter **4** to choose **Exit Rapid Deployment Pack Installation** and press the **Enter** key.



The Deployment Server installation is complete. However, before attempting to use the Deployment Server and perform Linux distribution scripted installs complete the procedures in Chapters 4 and 5.

## Multi-Server Installation

In performing a multi-server deployment infrastructure installation, both the DHCP Service and NFS Service can reside on servers other than the deployment server. The version of DHCP used must support the client classing and conditional behaviors required for PXE.

To use DHCP on a separate server:

- During the Altiris Deployment Server for Linux installation, enter **no** and press the **Enter** key when prompted for **Install the DHCP Server**.

To use a separate NFS server:

- During the Deployment Server installation, do not continue with the ProLiant Integration Module for NFS installation step.
- On a separate NFS server that meets the prerequisites, mount the Rapid Deployment Pack CD-ROM and run the Deployment Server setup script, `setup.sh`. Follow the steps in the “ProLiant Integration Module for NFS Server” section of this chapter, entering **3** to choose **ProLiant Integration Module for NFS Server** from the main menu to begin the ProLiant Integration Module for NFS Server installation.

## **Overview**

This section will provide information for upgrading any or all of the Rapid Deployment Pack components to a newer version as new versions become available.

---

# Pre-Deployment Configuration for the Deployment Server

## Overview

This chapter describes required and optional Deployment Server configuration modifications that must be performed before using the Deployment Server.

The following topics are discussed in this chapter:

- Configuring the access settings for Deployment Server for Linux Web console
- Synchronizing the Web console Display Name with the Linux Name
- Modifying the Primary Lookup Key
- Configuring ProLiant BL server enclosures
- Creating physical boot diskettes for server deployment


## Configuring the Access Settings for the Deployment Server for Linux Web Console

1. Access the Web console through a Web browser at <http://hostname:8080/webconsole>

where hostname is the host name of the Deployment Server or the static IP address of the Deployment Server in the form of xxx.xxx.xxx.xxx. For example:  
<http://192.168.1.1:8080/webconsole>.

**NOTE:** Initial access to each page will be sluggish because the Java Server Pages must be compiled. Subsequent page access will occur more quickly.

2. At the Database Connect window, enter the Deployment Server hostname or IP address. Click **Connect**.



The screenshot shows a web browser window with the address bar set to `/webconsole/default.jsp`. The page title is "Deployment Server Web Console". The main content area is titled "Database Connect" and contains the following text: "Please enter Deployment Database server name." Below this is a text input field labeled "Server name:" with a red asterisk indicating it is a required field. A legend below the field states " \* = Required field." At the bottom of the form is a "Connect" button. The left sidebar contains links for "Login" and "Install Agent Software". The top navigation bar includes "Login > Database Connect".

3. At the Console Login window, enter a password and click **Save**. This password is used to gain access to the Web console and should be retained for future use.

The screenshot shows a web browser window with the address bar displaying `/webconsole/default.jsp`. The page title is "Deployment Server Web Console". The left sidebar contains two links: "Login" and "Install Agent Software". The main content area is titled "Console registration page" and "Console Login". It contains a form with the following elements:

- A heading: "Please register for console."
- A "Password:" label followed by a text input field with a red asterisk.
- A "Confirm password:" label followed by a text input field with a red asterisk.
- A legend: "\* = Required field."
- A "Save" button.


Logos for HP and Altiris are visible in the top right corner of the page.

## Synchronizing the Web Console Display Name with the Linux Name

The Deployment Server has the capability to use a Web console display name that is different from the actual server hostname. However, you can select to have the Web console always reflect the same name as the server hostname.

To synchronize the Web console and server hostname:


1. At the Web console toolbar, click the **Program Options** icon. The **Program Options** information displays in the Details pane.
2. Select the **Global** tab.
3. Select **Synchronize display names with Linux computer names**.



4. Click **OK**.



- Click **OK** when prompted to restart the control servers.



## Modifying the Primary Lookup Key


The Deployment Server uses the primary lookup key to determine if a server is already in the database.

HP recommends setting the primary lookup key as the server serial number. Setting the primary lookup key as the server serial number has two benefits:

- It enables servers to be imported by their serial number, rather than keys that are more difficult to determine, such as the MAC address.
- It prevents duplicate database entries from occurring when servers have two or more NICs.


To change the primary lookup key to the server serial number:

1. At the Web console, click the **Program Options** icon in the toolbar. The **Program Options** information displays in the **Details** pane.
2. Select the **Global** tab.
3. From the Primary lookup key list, select **Serial Number (SMBIOS)**.



4. Click **OK**.

5. Click **OK** when prompted to restart the control servers.



## Configuring ProLiant BL Server Enclosures

The **Physical Devices** view in the Web console displays the physical relationship among the racks, enclosures, and blade servers using the rack name and enclosure name for each ProLiant BL server. The default name for the server rack is “UnnamedRack” and the default name for the BL e-Class server enclosure is the MAC address of the NIC associated with the Integrated Administrator.

Setting the rack name and enclosure name is recommended before the first server in an enclosure connects to the Deployment Server. After ProLiant BL servers are powered up for the first time and the rack and enclosure names are recorded in the Deployment Server database, the servers must be rebooted for new rack and enclosure names to be discovered. In addition, the default-named rack and enclosure must be manually deleted from the Web console.

## ProLiant BL e-Class Servers

To change the rack and enclosure names if the Integrated Administrator port is connected to a network with DHCP:

1. Browse to the DNS name located on the tag attached to the interconnect tray on the enclosure.
2. Log in to the Integrated Administrator using the user name and password located on the tag.
3. At the Enclosure Information screen, change the **Enclosure Name** and **Rack Name**, and then click **Apply**.

**IMPORTANT:** Do not use the same enclosure name for multiple enclosures. Using the same enclosure name will result in multiple blade servers being displayed in each bay for an enclosure and duplicate default server names.

The screenshot displays the HP ProLiant BL e-Class Integrated Administrator web interface. The top navigation bar includes the HP logo, the enclosure name '00508BEEF05A', the current user 'Administrator', and the title 'ProLiant BL e-Class INTEGRATED ADMINISTRATOR'. The left sidebar contains a menu with options: Enclosure, Bays, Administration, Event List, Interconnect, Enclosure Information, Network Configuration, SNMP Configuration, Virtual Buttons, and System Log. The main content area is titled 'Enclosure Information' and includes a prompt: 'Click the Apply button for all changes to take effect.' The interface is divided into two main sections: 'Status' and 'Power'. The 'Status' section shows the following details: Enclosure Name (00508BEEF05A), Rack Name (UnnamedRack), Enclosure Status (Degraded), Fan Status (Redundant Fans), Fan #1 (OK (40%)), Fan #2 (Standby), Fan #3 (OK (40%)), Fan #4 (Standby), Fan Spare Number (253079-001), Chassis Temperature (OK (91°F / 33°C)), Fan Exhaust Temperature (OK (84°F / 29°C)), and Blade Bay Temperature (OK (N/A)). The 'Power' section shows: Power Subsystem Status (Non-Redundant Power), Total Capacity (1200 Watts), and Power Supply #1 Status (OK). At the bottom of the form are 'Apply' and 'Cancel' buttons.

If the Integrated Administrator port is not connected to a network with DHCP, refer to the documentation shipped with the product for details concerning how to access the Integrated Administrator using other methods, such as the serial console.

After configuring the enclosure, install the ProLiant BL e-Class servers into the enclosure by following the instructions provided with the server hardware.

For more information regarding ProLiant BL e-Class servers, refer to the documentation shipped with the product.

## ProLiant BL p-Class Servers

To configure all racks and the ProLiant p-Class enclosure properly, at least one blade server must be placed in each enclosure. The blade server should not be powered on until the desired rack and enclosure names are set using the iLO interface. Otherwise, the blade server will boot to PXE (if enabled) and the default rack and enclosure name will be placed in the Deployment Server database.

After ProLiant BL servers are powered up for the first time and the rack and enclosure names are recorded in the Deployment Server database, the servers must be rebooted for new rack and enclosure names to be discovered. In addition, the default named enclosure and rack must be manually deleted from the Web console.

To change the rack and enclosure names if the iLO port is connected to the network with DHCP services available:

1. Browse to the DNS name located on the tag attached to the ProLiant BL p-Class server.
2. Log on to iLO using the credentials on the tag.

**NOTE:** Users that do not have the Administrator ProLiant BL p-Class privilege will only be able to view the settings.

3. Select the **BL p-Class** tab.
4. At the Rack Settings screen, change the **Rack Name** and **Enclosure Name**.

hp iLO INTEGRATED LIGHTS-OUT

Server Name: Administration  
iLO Name: iLO8319JTN8089E  
Logged in: Administrator

System Status Remote Console Virtual Devices Administration **BL p-Class** Insight Agent | Log out

### Rack Settings

**Rack Information**

Rack Name: North America Rack Serial Number: 2098DWA94E1  
Enclosure Name: Accounting Enclosure Serial Number: DY1962W40E88  
Bay Name: Accounts Payable Blade Serial Number: 68D0IYE10062  
Bay 8

**Power On Control**

Power Source: ☒ Rack Provides Power ☐ Facility Provides 48V  
Enable Automatic Power On: ☒ Yes ☐ No  
Enable Rack Alert Logging (IML): ☒ Yes ☐ No

Apply

**IMPORTANT:** Do not use the same enclosure name for multiple enclosures. Using the same enclosure name will result in multiple blade servers being displayed in each bay for an enclosure and duplicate default server names.

5. Click **Apply**.
6. After the parameter changes have been made, click **Apply** to complete the changes.
7. Log out, and log back on to iLO.

For more information regarding iLO, refer to the documentation shipped with the product.

If the iLO port is not connected to a network with DHCP services available, refer to the documentation provided with your blade server for details about accessing iLO from the front panel of the blade server.

## Creating Physical Boot Diskettes for Server Deployment

If PXE will not be used in the deployment infrastructure, one or more physical boot diskettes must be created. These diskettes enable target servers to communicate with the Deployment Server.

To create a DR-DOS boot diskette using the **Boot Disk Creator** within Altiris:

1. At the Web console toolbar, click the **Boot Disk Creator** icon. The Boot Disk Creator Web console opens.



2. Click the **Create a New Configuration** icon in the Boot Disk Creator Web Console toolbar.




3. In the Details pane, enter a name for the configuration, such as **DOS Boot Disk**, and a description, then click **Next**.

The screenshot shows a web browser window displaying the 'Boot Disk Creator Web Console'. The browser's address bar shows the URL `/bdc/index.jsp?serverName=rdple&userNam`. The console has a blue header bar with the title 'Boot Disk Creator Web Console' and logos for HP and Altiris. On the left, a sidebar contains a tree view with 'Configurations' and 'Additional Include Files'. The main content area has a 'Welcome' section with the instruction 'Enter name and description for your configuration.' Below this, there is a form with two fields: 'Enter a name for your configuration (i.e. "SalesInstall").' and 'Enter the detailed description of your configuration (optional) For example, "Network boot disk for sales laptops with 3C905 driver."'. The first field contains the text 'DOS Boot Disk'. A legend at the bottom of the form indicates that a red asterisk (\*) denotes a required field. At the bottom of the console, there is a footer bar with the Altiris Wizard logo, the text 'BootWorks Configuration Step 1 of 9', and three buttons: '< Back', 'Next >', and 'Cancel'.

4. Select **Bootworks boot disk** from the available choices. Select **Run the Initial Deployment for computers not already in the database**, and click **Next**.


**NOTE:** The Initial Deployment selection can be used on boot diskettes even when the computer is a managed computer, and Initial Deployment will only run the first time a computer displays in the Deployment Server.



## 5. Select the appropriate driver for the target server NIC.

- For Intel-based Gigabit NICs, select **HP –Intel Gigabit Adapter (n1000 .dos)**.
- For Intel 10/100 NICs, select **HP 10/100TX PCI LAN Adapter**.
- For Broadcom-based NICs, select **HP NC67xx/NC77xx Gigabit Ethernet**.

Verify **Use Intel universal NIC driver for Preboot Execution Environment (PXE)** is not selected. Click **Next**.



6. If static IP addresses are required, insert the appropriate information here. Click **Next** to accept the IP settings.

The screenshot shows a web browser window displaying the 'Boot Disk Creator Web Console'. The browser's address bar shows the URL `/bdc/index.jsp?serverName=rdple&userNam`. The console has a blue header with the title 'Boot Disk Creator Web Console' and logos for HP and Altiris. On the left, there is a sidebar with a tree view containing 'Configurations' and 'Additional Include Files'. The main content area is titled 'TCP/IP Protocol Settings' and contains the following text: 'The client computer will use TCP/IP to communicate to the Altiris Server. Select your TCP/IP settings for the client.' Below this text are two radio button options: 'Obtain an IP address from a DHCP server' (which is selected) and 'Use a static IP address. This IP address will be assigned to the client computer'. If the static IP option were selected, there would be input fields for 'IP address:', 'Subnet mask:', 'Default gateway:', 'Primary WINS server:', and 'Secondary WINS server:'. At the bottom of the console, there is a footer with the Altiris Wizard logo, the text 'BootWorks Configuration Step 4 of 9', and three buttons: '< Back', 'Next >', and 'Cancel'.


7. In the Use TCP/IP to connect to Altiris Server field, verify the Server IP address reflects the IP address of your Deployment Server. Click **Next**.

The screenshot shows the 'Boot Disk Creator Web Console' interface. The left sidebar contains 'Configurations' and 'Additional Include Files'. The main content area is titled 'Altiris Server Communication' and instructs the user to 'Select how the client computer will connect to the Altiris Server'. There are two radio button options: 'Use TCP/IP multicasting to find the Altiris Server' (selected) and 'Use TCP/IP to connect to Altiris Server'. The first option has input fields for 'IP address' (225.1.2.3), 'Port' (402), and 'Altiris Server name' (blank). The second option has input fields for 'Server IP address' (blank) and 'Port' (402). At the bottom, the 'altiris Wizard' logo is displayed, along with the text 'BootWorks Configuration Step 5 of 9' and navigation buttons: '< Back', 'Next >', and 'Cancel'.


8. Click **Next** to accept the default workgroup name and login account settings.

The screenshot shows the 'Boot Disk Creator Web Console' interface. The left sidebar contains 'Configurations' and 'Additional Include Files'. The main content area is titled 'Network Connection' and instructs the user to 'Enter your network settings for the client computer. These will be used to connect to your file server.' There is a text input field for 'Domain/Workgroup' with the value 'workgroup'. Below this, there is a section for 'Enter the account information that will be used to connect to your file server.' with input fields for 'User name' (leuser), 'Password' (masked with asterisks), and 'Confirm password' (masked with asterisks). A note at the bottom states '\* = Required field.' At the bottom of the console, the 'altiris Wizard' logo is displayed, along with the text 'BootWorks Configuration Step 6 of 9' and navigation buttons: '< Back', 'Next >', and 'Cancel'.

9. Click **Next** to accept the default drive mappings settings.




10. Click **Finish** to create the configuration.




11. Click **Close**.

12. From the Boot Disk Creator Web Console toolbar, click the **Create Disks** icon. The Details pane displays the Choose Configuration selections.
13. Select the newly created configuration (“DOS Boot Disk” in this example) and click **Next**.
14. Select **Download disk images at client** and click **Next**.



15. Click the boot disk image link (bootdiskimage.img) referred to in the **Disk Image Creation Complete** instructions and follow the on-screen instructions. Note the additional instructions to convert the file while copying the image onto a floppy diskette.

Boot Disk Creator uses the same image file name of bootdiskimage.img. If you are saving multiple configurations, use different names when saving to your drive.



16. When the image is saved to the drive, click **Close**.
17. At a Linux prompt, duplicate the image onto a floppy using the instructions from step 16 that were displayed in the Disk Image Creation Complete window.



---

## Pre-Deployment Configuration for Linux Scripted Installs

### Overview

This chapter describes required modifications that must be performed before using any Linux scripted install jobs.

The following topics are covered in this chapter:

- Preconfiguring the ProLiant Support Pack for Linux
- Preconfiguring deployment settings for Red Hat Linux scripted install jobs
- Preconfiguring deployment settings for UnitedLinux scripted install jobs

## Preconfiguring the ProLiant Support Pack for Linux

The Web-based Management portion of the Foundation Agents requires that a password be configured before installation. This password is also used by several other components in the ProLiant support software. Without the password, the Web-based Management portion of the Foundation Agents will install but will not function correctly or be accessible on your deployed servers.

Support software directories and scripts associated with each Linux operating system are located on the NFS server. These files are located at `/usr/cpqrdrp/ss.xxx/yyyy/csp`, where `xxx` is the ProLiant Support Pack version and `yyyy` is the Linux distribution shortcut name, such as `rhas21` for Red Hat Enterprise Linux AS 2.1. A support software script, `yyyy.sh`, is used to install the ProLiant support software, and within this script are the password variables for the Linux Web Agent.

Additionally, SNMP settings are configured in this script.

The Linux Web Agent default passwords are listed in Table 5-1.

**Table 5-1: Linux Web Agent Default Passwords**

User Name	Password
administrator	password
operator	password
user	password


Because the default passwords are documented here, HP recommends changing the passwords either by editing the support software script as previously described or by browsing to the installed server, port 2301 or secured port 2381, and changing the password. Changing the password by editing the support software script before a scripted install means these passwords can be mass deployed to target servers. Additionally, after the scripted install, modified passwords can be replicated to other servers by copying the `/var/spool/compaq/wbem/cpqhmmmd.acl` file to other servers.

## Preconfiguring Deployment Settings for Red Hat Linux Scripted Install Jobs


For the Red Hat Linux scripted install jobs to work, they must be modified with the host and domain name or IP address of the NFS server on which the installation files are located.

To update each Red Hat Linux scripted install job to point to the NFS server:

1. Locate the Red Hat Linux scripted install jobs to be modified within the Web console. Expand the tree view, if necessary, to view the jobs in the Jobs pane.
2. Click the job to highlight it. The job properties information displays in the Details pane.



- Click the last **Run Script** link of the Install OS – Run Script task. The run script properties information displays in the Details pane.



- Locate the following line in the script:  
`set nfsserver=0.0.0.0`
- Change 0.0.0.0 to the host and domain name of the NFS server as follows:

```
set nfsserver=yournfssvr.yourdomain
```

where *yournfssvr* is the host name of the NFS server, and *yourdomain* is the domain name for the NFS server.

Instead of a host name and domain name, an IP address can be specified as follows:

```
set nfsserver=xxx.xxx.xxx.xxx
```

where *xxx.xxx.xxx.xxx* is the fixed IP address of the NFS server.

**NOTE:** Using the IP address to connect to the NFS server is more effective than using a DNS name, since using a DNS name requires the existence of a DNS server properly configured with an entry for the NFS server.


- Click **Apply** to save changes.
- Repeat steps 2 through 6 for any remaining Red Hat Linux scripted install jobs.

## Preconfiguring Deployment Settings for UnitedLinux Scripted Install Jobs


For the UnitedLinux scripted install jobs to work properly, they must be modified with the host and domain name or IP address of the NFS server where the installation files are located.

To update each UnitedLinux scripted install job to point to the NFS server:

1. Locate the UnitedLinux scripted install jobs to be modified within the Deployment Server Console. Expand the tree view, if necessary, to view the jobs in the Jobs pane.
2. Click the job to highlight it. The job properties information displays in the Details pane.



- Click the last **Run Script** link of the Install OS – Run Script task. The run script properties information displays in the Details pane.



- Locate the following line in the script:  
`set nfsserver=0.0.0.0`
- Change 0.0.0.0 to the host and domain name of the NFS server as follows:

```
set nfsserver=yournfssvr.yourdomain
```

where *yournfssvr* is the host name of the NFS server, and *yourdomain* is the domain name of the NFS server.

Instead of a host name and domain name, an IP address can be specified as follows:

```
set nfsserver=xxx.xxx.xxx.xxx
```

where *xxx.xxx.xxx.xxx* is the fixed IP address of the NFS server.

Using the IP address to connect to the NFS server is more effective than using a DNS name, since using a DNS name requires the existence of a DNS server properly configured with an entry for the NFS server.

- Click **Apply** to save changes.
- Repeat steps 2 through 6 for any remaining UnitedLinux scripted install jobs.

---

## Manually Installing Red Hat Enterprise Linux Boot Files

If you chose to not copy the Red Hat Enterprise Linux boot files during installation, then you must manually copy those files for each distribution skipped for the Red Hat Enterprise Linux provided jobs to work.

**NOTE:** Linux boot files for all other Linux distributions are provided on the Rapid Deployment Pack CD and installed during the ProLiant Integration Module for Linux Deployment Server installation.

To manually copy the Red Hat Enterprise Linux boot files to the Deployment Server directory:

1. Locate the `/opt/altiris/deployment/adlserver/deploy/cds/compaq/ss.xxx/yyyy` directory on the Deployment Server, where `xxx` is the ProLiant Support Pack version and `yyyy` is the Linux distribution shortcut name for the distribution you skipped.

Linux Distribution	Distribution Shortcut Name
Red Hat Enterprise Linux AS 2.1	rhas21
Red Hat Enterprise Linux ES 2.1	rhes21

**IMPORTANT:** The copied boot files must match the distribution version copied during the “ProLiant Integration Module for NFS Server” installation or during the “Manually Installing Linux Distribution CDs.”

2. Insert the first distribution CD into the Deployment Server CD-ROM drive.
3. Mount the CD-ROM drive:

```
mount /mnt/cdrom (Red Hat)
or
mount /media/cdrom (UnitedLinux)
```

4. Copy the following files into the Deployment Server directory from Red Hat Linux CD #1 as shown in Table A-1.

**Table A-1: File Sources and Destinations**

Source	Destination
/dosutils/loadlin.exe	/opt/altiris/deployment/adlserver/deploy/cds/compaq/ss.xxx/yyyy/ dosutils/loadlin.exe
/images/pxeboot/vmlinuz	/opt/altiris/deployment/adlserver/deploy/cds/compaq/ss.xxx/yyyy/ dosutils/autoboot/vmlinuz
/images/pxeboot/initrd- everything.img	/opt/altiris/deployment/adlserver/deploy/cds/compaq/ss.xxx/yyyy/ dosutils/autoboot/initrd.img

**NOTE:** Rename the copied initrd-everything.img file to initrd.img.

5. Unmount the CD-ROM drive:

```
umount /mnt/cdrom (Red Hat)
```

or

```
umount /media/cdrom (UnitedLinux)
```



---

## Manually Installing Linux Distribution CDs

If you chose to not copy the Linux distribution CDs during installation, then you must manually copy those Linux files for each distribution skipped for the provided jobs corresponding to the Linux version to work.

To manually copy a set of Linux distribution CDs to the NFS server directory:

1. Locate the /usr/cpqrdp/yyyy directory on the NFS server, where yyyy is the Linux distribution shortcut name for the distribution you skipped.

Linux Distribution	Distribution Shortcut name
Red Hat Enterprise Linux AS 2.1	rhas21
Red Hat Enterprise Linux ES 2.1	rhes21
Red Hat 7.2	rh72
Red Hat 7.3	rh73
Red Hat 8.0 Professional	rh80

**IMPORTANT:** The copied Red Hat Enterprise Linux distribution files must match the boot files version copied during the “ProLiant Integration Module for Linux Deployment Server” installation or during “Manually Installing Red Hat Enterprise Linux Boot Files.”

2. Insert the first distribution CD into the NFS server CD-ROM drive.
3. Mount the CD-ROM drive:

```
mount /mnt/cdrom (Red Hat)
```

or

```
mount /media/cdrom (UnitedLinux)
```

4. Copy the contents of the distribution CD, including subdirectories, to the distribution directory. For example:

```
cp -r /mnt/cdrom/* /usr/cpqrdp/rhas21
```

5. Unmount the CD-ROM drive:

```
umount /mnt/cdrom (Red Hat)
```

or

```
umount /media/cdrom (UnitedLinux)
```

6. Repeat steps 3 through 5 to copy the remaining CDs in the distribution set. The distribution CDs containing the RedHat/RPMS directory is required. However, not all distribution CDs in the set might be needed.

---

# Index

## A

- access settings configuration 4-2
- Altiris Deployment Server for Linux installation 2-9
- Altiris Deployment Server for Linux requirements 2-4

## B

- BL server enclosures configuration 4-8
- boot diskette creation 4-12
- boot files A-1

## C

- configuration
  - BL server enclosures 4-8
  - Linux operating system 5-3, 5-5
  - network requirements 2-4
  - ProLiant BL servers 4-8
  - system requirements 2-4

## D

- deployment infrastructure 2-2
- deployment infrastructure multi-server 2-3
- Deployment Server Console
  - access settings 4-2
  - accessing 4-2
  - Primary Lookup Key 4-5
  - synchronizing name 4-4
- Deployment Server requirements 2-4
- DHCP support 2-4
- diskette boot 4-12

## E

- enclosure name 4-8

## F

- firewall 2-5, 2-6
- Foundation Agents 5-2

## H

- hardware requirements 2-4
- HP authorized reseller vi

## I

- imaging jobs 2-17
- installation
  - Altiris Deployment Server for Linux 2-9
  - basic 2-7
  - Deployment Server 2-7
  - jobs 2-17
  - Linux distribution files manual
    - installation A-1, B-1
  - multi-server 2-25
  - ProLiant Integration Module for Linux
    - Deployment Server 2-16
  - ProLiant Integration Module for NFS
    - Server 2-21
  - Rapid Deployment Pack 2-7
  - requirements 2-4
- Integrated Administrator 4-8
- Integrated Lights-Out 4-8

## J

- jobs deployment 2-17

## L

- licenses
  - applying during a first time installation 1-3
  - applying to an existing installation 1-3
  - evaluation 1-2
  - obtaining 1-2
  - purchased 1-2
  - replacing 1-4
- licensing options 1-1
- Linux distribution files manual installation A-1, B-1
- Linux operating system configuration 5-3, 5-5

## M

- multi-server installation 2-25

## N

NFS Server  
    installation 2-21  
    job setup 5-3, 5-5  
    Linux distribution files manual  
        installation A-1, B-1  
    requirements 2-6

## O

operating systems  
    manual installation B-1  
    synchronizing 4-4

## P

passwords  
    changing 5-2  
    default 5-2  
physical boot diskettes creation 4-12  
Physical Devices view 4-8  
ports firewall 2-5, 2-6  
PostgreSQL 2-5, 2-11  
Primary Lookup Key modification 4-5  
ProLiant BL servers  
    configuration 4-8  
    Physical Devices view 4-8  
ProLiant Integration Module for NFS Server 2-21  
ProLiant servers supported 2-6  
ProLiant Support Pack 5-2  
ProLiant Support Pack for Linux  
    preconfiguration 5-2  
PXE support 2-6

## R

rack name 4-8  
Rapid Deployment Pack installation 2-6, 2-7  
Red Hat Linux  
    configuration 5-3  
    scripted install jobs 5-3  
remote management Integrated Lights-Out 4-8

requirements

    Deployment Server 2-4  
    installation 2-4  
    Linux Deployment Server 2-4  
    network infrastructure 2-4  
    NFS Server 2-6

## S

SAMBA 2-5  
scripted installation  
    jobs 2-17  
    Red Hat Linux 5-3  
    UnitedLinux 5-5  
Smart Components 5-2  
software installation 2-7  
support target server 2-6  
synchronizing display name 4-4

## T

target servers support 2-6  
telephone numbers vi

## U

UnitedLinux  
    configuration 5-5  
    Deployment Server 2-4  
    NFS Server 2-6  
    scripted install jobs 5-5  
UnitedLinux components 2-4

## W

Web console  
    access settings 4-2  
    Primary Lookup Key 4-5  
    synchronizing names 4-4  
Web-based Management 5-2  
Windows operating systems synchronizing  
    names 4-4